

Maximum permitted weights and dimensions, goods transport Turkey

| Height | ارتفاع | 4.00m |
|------------------------------------------------------------------------------------------------|--------------------------------------|----------------|
| Width | لنهر | |
| Motor vehicle/trailer | وسائط نقلیه موتوری/تریلر | 2.55m |
| Refrigerated vehicle | کامیونهای یخچالی | 2.60m |
| Length | طول طول | |
| Motor vehicle | | |
| with 2 axles | وسائط نقليه موتورى | 12.00m |
| with 3 axles or more | کامیونهای مفصل دار | 12.00m |
| Articulated vehicle Road train | تامیونهای مفصل دار قطارکها | 16.50m |
| · lorry + 1 trailer | ` - | 18.75m |
| lorry + 2 trailers | کامیون + ۱ تریلر | 22.00m |
| Weight per axle | کامیون + ۲ تریلر | |
| single non-drive axle | وزن هر محور | 10.0t |
| single drive axle | محور منفرد غيرمتحرك | 11.5t |
| tandem axle, with a distance between the axles of | محور متفرد متحرك | |
| <1.00m | محور مرکب، یا فاصله یین هر محور | 11.5t |
| · 1.00m to 1.30m | | 16.0t |
| · 1.30m to 1.80m · >1.80m | | 18.0t 20.0t |
| tridem axle, with a distance between the axles of | محورهای ۳ گانه، با فاصله بین هر محور | 20.01 |
| ·<1.30m | محورهای ۱ کامه با فاصله بین هر محور | 21.0t |
| · 1.30m to 1.40m | | 24.0t |
| Maximum permitted weight | حداكثر وزن مجاز | |
| Motor vehicle | وسائط نقلیه موتوری | |
| · with 2 axles | 3 33 7 , | 18.0t |
| with 3 axles | | 25.0t |
| with 4 axles | | 32.0t |
| Articulated vehicle | کامیونها ی مفصل دار | 00.04 |
| · with 3 axles · with 4 axles | | 28.0t 36.0t |
| · with 4 axies · with 4 axies, and the weight of the tandem axie of the semi-trailer is 20t | | 38.0t |
| with 5/6 axies | | 40.0t |
| with 5/6 axles for the combined transport of a 40' ISO container | | 44.0t |
| Road train | | |
| with 4 axies | قطاركها | 36.0t |
| with 5/6 axles | | 40.0t |

Source: UND, May 2015